



Pellet Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 7,0
Introduced thermal power (at max)	kW	7,7
Seasonal energy efficiency	ηs [%]	86
Useful efficiency (at min-at max)	%	91,0 - 90,0
Heating surface (at min-at max)	m ²	26,4 - 73,9
CO ₂ (min-max)	%	6,8 - 12,8
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	238 - 42
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	1 - 4
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	140 - 117
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	20 - 15
Combustible Pellet	mm	ø6 L3÷40
Hopper capacity	kg	15
Hourly consumption (at min-at max)	kg/h	0,60 - 1,70
Autonomy (at min-at max)	h	25 - 9
Supply and frequency	V-Hz	230-50
Ignition electrical absorption (at max)	W	345
Operating electrical absorption (at max)	W	49
Chimney flue depression (at min-at max)	Pa	2 - 10
Mass of smoke (at min-at max)	g/sec	2,6 - 4,6
Exhaust fumes temperature (at min-at max)	°C	113 - 190
Distance from material comb. (back/side/under)	mm	200 / 300 / 0
Distance to material comb. (front/top)	mm	1000 / 0
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Ducting outlet (C)	Ø mm	0
Ductable up to	m	0

PLUS



AVAILABLE FINISHES

7020527		Steel Anthracite	EAN 8053859014553
7020528		Steel White	EAN 8053859014560
7020529		Steel Red Bordeaux	EAN 8053859014577

OPTIONAL

5018012	CONCENTRIC KIT 80F-130F (FR)	EAN 8053859010364
5019012	PELLET STOVE REMOTE CONTROL	EAN 8053859011965
5018011	CONCENTRIC KIT 80F-130M (FR)	EAN 8053859010357

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen

EN 14785:2006



STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	117	60
	Volume (m ³)	0,56	
	Gross weight (kg)	66	
	Net weight (kg)	56	

STORAGE

	N° (max)
MAX 2	2
1	

TRANSPORT

66 pz