










Pellet Air Plus

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,5 - 8,5
Introduced thermal power (at max)	kW	9,7
Water useful power (at min-at max)	kW	-
Seasonal energy efficiency	η_s [%]	83
Useful efficiency (at min-at max)	%	90,0 - 87,0
Heating surface (at min-at max)	m ²	25,9 - 88,2
CO ₂ (min-max)	%	6,3 - 12,0
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	297 - 160
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	5 - 3
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	120 - 140
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	20 - 15
Combustible Pellet	mm	ø6 L31-40
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	17
Hourly consumption (at min-at max)	kg/h	0,60 - 2,10
Autonomy (at min-at max)	h	28 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption (at max)	W	340
Operating electrical absorption (at max)	W	106
Chimney flue depression (at min-at max)	Pa	2 - 12
Mass of smoke (at min-at max)	g/sec	3,1 - 6,0
Exhaust fumes temperature (at min-at max)	°C	120 - 253
Distance from material comb. (back/side/under)	mm	200 / 300 / 15
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	50
Ducting outlet (C)	Ø mm	80
Ductable up to	m	7

PLUS

 Concentric flue kit (optional)	 Cast iron door	 Sealed chamber
 Cast iron burning pot	 Duction with 1 independent motor	 Comfort mode - Maximum silence
 Integrated Wi-Fi and Bluetooth	 Connection to the external therm.	 7 settimanale / Daily weekly

AVAILABLE FINISHES

7022050		Steel White	EAN 8053859015178
7022051		Steel Red Bordeaux	EAN 8053859015185
7022052		Steel Anthracite	EAN 8053859015192

OPTIONAL

5020003	EAN 8053859012573
5022001	EAN 8053859015536
5022003	EAN 8053859015550


CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen


EN 14785:2006
CE




STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	118	61
	Volume (m ³)	0,58	
	Peso lordo (kg)	85	
	Peso netto (kg)	75	

STORAGE

	N° (max)
	2
MAX 2	
1	

TRANSPORT


66 pz